C-Lube Linear Way ML
Linear Way L

C-Lube Linear Way ML

ML

C-Lube Maintenance-free
long term maintenance free supported!

Linear Way L

LWL

Points

1 Extremely small size realized by simple structure

For details ➔ P.I-19

Super small-size linear motion rolling guide produced by two-row four-point contact simple structure and original small sizing technology. The track rail width of LWL1, the smallest size, is only 1mm.

2 Wide range of variations for your needs

For details ➔ P.I-25

The slide unit shape can be selected from two types, the standard type and the wide type suited for single-row track rail uses, and there are four types with different lengths of slide unit with same section. Furthermore, the track rail has the variation of standard type and tapped rail type with the screw thread implanted, allowing you to select an optimal product for the specifications of your machine and device.

3 Ball retained type for easy operation

The slide unit of ball retained type incorporates the ball retaining band, which prevents the ball from dropping down when the slide unit is removed from the track rail. This safety structure brings you an easy operation to the machines / equipment.

4 Stainless steel selections for excellent corrosion resistance

For details ➔ P.I-43

Stainless steel highly corrosion-resistant is used as the basic specification, so that the products are suitable for applications where rust prevention oil is not preferred, such as in cleanroom environment. High carbon steel products suited to general purposes are also provided.

5 Widely supports special environment uses

For details ➔ P.I-33

C-Lube Linear Way ML for special environment uses are provided as a series. Increasingly varied special environment uses are supported, such as by high-speed / low-noise specifications by combining silicon nitride ceramics and low dust-generation specifications.

Identification Number and Specification

Example of an identification number

The specifications of ML(F) and LWL(F) series are indicated by the identification number. Indicate the identification number, consisting of a model code, dimensions, a part code, a material code, a preload symbol, a classification symbol, an interchangeable code, and any supplemental codes for each specification to apply.

	1	2	4	5	6	3	7	8	9	10	11
Non-interchangeable specification											
Assembled set	ML	C	12	C1	R200			T_1	P		/U
Interchangeable specification											
Single slide unit	ML	C	12	C1				T_1	P	S1	/U
Single track rail (1)	LWL		12		R200	B			P	S1	
Assembled set	ML	C	12	C1	R200			T_1	P	S1	/U

1 Model
2 Length of slide unit
3 Structure
→ Model code Page Ⅱ－7

4 Size
→ Dimensions Page Ⅱ－7

5 Number of slide units
6 Length of track rail
→ Part code Page Ⅱ－7

7 Material type
→ Material code Page Ⅱ－7

8 Preload amount
→ Preload symbol Page Ⅱ－13

9 Accuracy class
→ Classification symbol Page Ⅱ－14

10 Interchangeable
→ Interchangeable code Page Ⅱ－15

11 Special specification
→ Supplemental code Page Ⅱ－15

Note (1) Indicate "LWL···B" or "LWLF···B" for the model code of the single track rail regardless of the series and the combination of slide unit models.

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Identification Number and Specification — Model · Length of Slide Unit ·

1 Model

C-Lube Linear Way ML (ML(F) series)
Standard type : ML
Wide type : MLF

Linear way L (1) (LWL (F) series)
Standard type : LWL
Wide type : LWLF

For applicable models and sizes, see Table 2.1 and Table 2.2.
Indicate "LWL···B" or "LWLF···B" for the model code of the single track rail regardless of the series and the combination of slide unit models.

Note (1) This model has no built-in C-Lube.

2 Length of slide unit

Short : C
Standard : No symbol
Long : G
Extra long : L

For applicable models and sizes, see Table 2.1 and Table 2.2.

3 Structure

Table 1.1 Structure of ML and LWL

Model	Types and sizes of track rails			Structure	
ML	Standard rail specification		Size: 5～25	Ball retained type	: No symbol
	Tapped rail specification		Size: 3	Ball non-retained type	: No symbol
			Size: 5, 7, 9	Ball retained type	: N
LWL	Standard rail specification			Ball retained type	: B
	Tapped rail specification	Mounting from bottom	Size: 2, 3	Ball non-retained type	: No symbol
			Size: 5, 7, 9	Ball retained type	: N
		Mounting from lateral	Size: 1	Ball non-retained type	: Y
	Solid rail specification		Size: 1	Ball non-retained type	: No symbol

Table 1.2 Structure of MLF and LWLF

Model	Types of track rails			Structure	
MLF	Standard rail specification		Size: 6	Ball non-retained type	: No symbol
			Size: 10～42	Ball retained type	
	Tapped rail specification		Size: 6	Ball non-retained type	: N
			Size: 10～18	Ball retained type	
LWLF	Standard rail specification		Size: 4, 6	Ball non-retained type	: No symbol
			Size: 10～42	Ball retained type	: B
	Tapped rail specification		Size: 2	Ball non-retained type	: No symbol
			Size: 6	Ball non-retained type	: N
			Size: 10～18	Ball retained type	

For applicable models and sizes, see Table 2.1 and Table 2.2.

4 Size

Standard type 1, 2, 3, 5, 7, 9, 12, 15, 20, 25
Wide type 2, 4, 6, 10, 14, 18, 24, 30, 42

For applicable models and sizes, see Table 2.1 and Table 2.2.

5 Number of slide units

: C○

For an assembled set, indicates the number of slide units assembled on a track rail. For a single slide unit, only "C1" is specified.

6 Length of track rail

: R○

Indicate the length of track rail in mm.
For standard and maximum lengths, see Table 3.1, Table 3.2, and Table 3.3.

7 Material type

Stainless steel made : No symbol
High carbon steel made : CS

For applicable models and sizes, see Table 2.1 and Table 2.2.

Structure · Size · Number of Slide Unit · Length of Track Rail · Material Type —

Table 2.1 Models and sizes of standard type ML(F) and LWL(F) series

Types of track rails	Material type	Length of slide unit	Structure	Model	Size 1	2	3	5	7	9	12	15	20	25
Standard rail specification	Stainless steel made	Short 	Ball retained type	MLC	–	–	–	○	○	○	○	○	○	○
				LWLC···B	–	–	–	○	○	○	○	○	○	○
		Standard 		ML	–	–	–	○	○	○	○	○	○	○
				LWL···B	–	–	–	○	○	○	○	○	○	○
		Long 		MLG	–	–	–	–	○	○	○	○	○	○
				LWLG···B	–	–	–	–	○	○	○	○	○	○
		Extra long 		MLL	–	–	–	–	–	○	○	○	–	–
	High carbon steel made	Standard 		LWL···BCS	–	–	–	–	–	○	○	○	○	–
Tapped rail specification Mounting from bottom	Stainless steel made	Short 	Ball non-retained type	MLC	–	–	○	–	–	–	–	–	–	–
				LWLC	–	–	○	–	–	–	–	–	–	–
			Ball retained type	MLC···N	–	–	–	○	○	○	–	–	–	–
				LWLC···N	–	–	–	○	○	○	–	–	–	–
		Standard 	Ball non-retained type	ML	–	–	○	–	–	–	–	–	–	–
				LWL	–	○	○	–	–	–	–	–	–	–
			Ball retained type	ML···N	–	–	–	○	○	○	–	–	–	–
				LWL···N	–	–	–	○	○	○	–	–	–	–
		Long 	Ball retained type	MLG···N	–	–	–	–	○	○	–	–	–	–
				LWLG···N	–	–	–	–	○	○	–	–	–	–
		Extra long 	Ball retained type	MLL···N	–	–	–	–	–	○	–	–	–	–
Tapped rail specification Mounting from lateral		Standard 	Ball non-retained type	LWL···Y	○	–	–	–	–	–	–	–	–	–
Solid rail specification		Standard 	Ball non-retained type	LWL	○	–	–	–	–	–	–	–	–	–

Remark: For the models indicated in ▭, the interchangeable specification is available.

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Table 2.2 Models and sizes of wide type ML(F) and LWL(F) series

Types of track rails	Material type	Length of slide unit	Structure	Model	Size 2	4	6	10	14	18	24	30	42
Standard rail specification	Stainless steel made	Short	Ball retained type	MLFC	–	–	–	○	○	○	○	○	○
				LWLFC···B	–	–	–	○	○	○	○	○	○
			Ball non-retained type	MLFC	–	–	○	–	–	–	–	–	–
				LWLFC	–	–	○	–	–	–	–	–	–
		Standard	Ball retained type	MLF	–	–	–	○	○	○	○	○	○
				LWLF···B	–	–	–	○	○	○	○	○	○
			Ball non-retained type	MLF	–	–	○	–	–	–	–	–	–
				LWLF	–	○	○	–	–	–	–	–	–
		Long 	Ball retained type	MLFG	–	–	–	–	○	○	○	○	○
				LWLFG···B	–	–	–	–	○	○	○	○	○
	High carbon steel made	Standard 	Ball retained type	LWLF···BCS	–	–	–	–	–	○	○	○	○
Tapped rail specification Mounting from bottom	Stainless steel made	Short 	Ball retained type	MLFC···N	–	–	–	○	○	○	–	–	–
				LWLFC···N	–	–	–	○	○	○	–	–	–
			Ball non-retained type	MLFC···N	–	–	○	–	–	–	–	–	–
				LWLFC···N	–	–	○	–	–	–	–	–	–
		Standard 	Ball retained type	MLF···N	–	–	–	○	○	○	–	–	–
				LWLF···N	–	–	–	○	○	○	–	–	–
			Ball non-retained type	MLF···N	–	–	○	–	–	–	–	–	–
				LWLF···N	–	–	○	–	–	–	–	–	–
		Long 	Ball retained type	MLFG···N	–	–	–	–	○	○	–	–	–
				LWLFG···N	–	–	–	–	○	○	–	–	–
		Standard	Ball non-retained type	LWLF	○	–	–	–	–	–	–	–	–

Remark: For the models indicated in ▭, the interchangeable specification is available.

Table 3.1 Standard and maximum length of stainless steel track rail (Standard type)



unit: mm

Item \ Identification number	LWL1···Y	LWL1	LWL2	ML 3 LWL3	ML 5 (4) LWL5···B (4)	ML 7 (4) LWL7···B (4)
Standard length L (n)	18 (3) 30 (5) 42 (7)	18 (−) 30 (−) 42 (−)	32 (4) 40 (5) 56 (7) 80 (10)	30 (3) 40 (4) 60 (6) 80 (8) 100 (10)	60 (4) 90 (6) 105 (7) 120 (8) 150 (10)	60 (4) 90 (6) 120 (8) 150 (10) 180 (12) 240 (16)
Pitch of mounting holes F	6	–	8	10	15	15
E	3	–	4	5	7.5	7.5
Standard E dimensions (1) or higher	2.5	–	2.5	3	4	4.5
Standard E dimensions (1) below	5.5	–	6.5	8	11.5	12
Maximum length (2)	102	102	104 (200)	150 (300)	210 (510)	300 (990)
Maximum number of butt-jointing track rail (3)	–	–	–	–	5	7
Maximum length of butt-jointing track rail (3)	–	–	–	–	915	1 905

Item \ Identification number	ML 9 (4) LWL9···B (4)	ML 12 LWL12···B	ML 15 LWL15···B	ML 20 LWL20···B	ML 25 LWL25···B
Standard length L (n)	60 (3) 80 (4) 120 (6) 160 (8) 220 (11) 280 (14)	100 (4) 150 (6) 200 (8) 275 (11) 350 (14) 475 (19)	160 (4) 240 (6) 320 (8) 440 (11) 560 (14) 680 (17)	180 (3) 240 (4) 360 (6) 480 (8) 660 (11) 840 (14)	240 (4) 300 (5) 360 (6) 480 (8) 660 (11) 900 (15)
Pitch of mounting holes F	20	25	40	60	60
E	10	12.5	20	30	30
Standard E dimensions (1) or higher	4.5	5	5.5	8	9
Standard E dimensions (1) below	14.5	17.5	25.5	38	39
Maximum length (2)	860 (1 200)	1 000 (1 450)	1 000 (1 480)	960 (1 800)	960 (1 800)
Maximum number of butt-jointing track rail (3)	2	2	2	2	2
Maximum length of butt-jointing track rail (3)	1 660	1 925	1 880	1 740	1 740

Notes (1) Not applicable to track rail with stopper pins (supplemental code "/S").
(2) Length up to the value in ( ) can be produced. If needed, please contact IKO.
(3) Not applicable to interchangeable specifications or tapped rail specifications.
(4) Also applicable to tapped rail specification.

Remarks 1. A typical identification number is indicated, but is applied to all models of the same size.
2. Indicate "LWL···B" for the model code of the single track rail regardless of the series and the combination of slide unit models.
3. If not directed, E dimensions for both ends will be the same within the range of standard E dimensions. To change the dimensions, indicate the specified rail mounting hole positions "/E" of special specification. For more information, see page Ⅲ−30.

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Table 3.2 Standard and maximum length of stainless steel track rail (Wide type)



unit: mm

Item \ Identification number	LWLF2	LWLF4	MLF 6 (4) LWLF6 (4)	MLF 10 (4) LWLF10···B (4)	MLF 14 (4) LWLF14···B (4)
Standard length L (n)	18 (3) 30 (5) 42 (7) 54 (9)	40 (4) 60 (6) 70 (7) 80 (8) 100 (10)	60 (4) 90 (6) 105 (7) 120 (8) 150 (10)	60 (3) 80 (4) 120 (6) 160 (8) 220 (11) 280 (14)	90 (3) 120 (4) 150 (5) 180 (6) 240 (8) 300 (10)
Pitch of mounting holes F	6	10	15	20	30
E	3	5	7.5	10	15
Standard E dimensions (1) or higher	2.5	3.5	4.5	4.5	5.5
Standard E dimensions (1) below	5.5	8.5	12	14.5	20.5
Maximum length (2)	102	180 (300)	240 (300)	300 (500)	300 (990)
Maximum number of butt-jointing track rail (3)	–	–	–	7	8
Maximum length of butt-jointing track rail (3)	–	–	–	1 840	1 950

Item \ Identification number	MLF 18 (4) LWLF18···B (4)	MLF 24 LWLF24···B	MLF 30 LWLF30···B	MLF 42 LWLF42···B
Standard length L (n)	90 (3) 120 (4) 150 (5) 180 (6) 240 (8) 300 (10)	120 (3) 160 (4) 240 (6) 320 (8) 400 (10) 480 (12)	160 (4) 240 (6) 320 (8) 440 (11) 560 (14) 680 (17)	160 (4) 240 (6) 320 (8) 440 (11) 560 (14) 680 (17)
Pitch of mounting holes F	30	40	40	40
E	15	20	20	20
Standard E dimensions (1) or higher	5.5	6.5	6.5	6.5
Standard E dimensions (1) below	20.5	26.5	26.5	26.5
Maximum length (2)	690 (1 860)	680 (1 960)	680 (2 000)	680 (2 000)
Maximum number of butt-jointing track rail (3)	3	3	3	3
Maximum length of butt-jointing track rail (3)	1 920	1 840	1 840	1 840

Notes (1) Not applicable to track rail with stopper pins (supplemental code "/S").
(2) Length up to the value in ( ) can be produced. If needed, please contact IKO.
(3) Not applicable to interchangeable specifications or tapped rail specifications.
(4) Also applicable to tapped rail specification.

Remarks 1. A typical identification number is indicated, but is applied to all models of the same size.
2. Indicate "LWLF···B" for the model code of the single track rail regardless of the series and the combination of slide unit models.
3. If not directed, E dimensions for both ends will be the same within the range of standard E dimensions. To change the dimensions, indicate the specified rail mounting hole positions "/E" of special specification. For more information, see page Ⅲ−30.

Table 3.3 Standard and maximum length of high carbon steel track rail (Standard type, Wide type)



unit: mm

Item \ Identification number	LWL 9···BCS	LWL12···BCS	LWL15···BCS	LWL20···BCS
Standard length L (n)	80 (4) 160 (8) 220 (11) 280 (14) 380 (19) 500 (25) 600 (30)	100 (4) 200 (8) 275 (11) 350 (14) 475 (19) 600 (24) 700 (28)	160 (4) 320 (8) 440 (11) 560 (14) 680 (17) 800 (20) 920 (23)	180 (3) 240 (4) 360 (6) 480 (8) 660 (11) 900 (15) 1 020 (17)
Pitch of mounting holes F	20	25	40	60
E	10	12.5	20	30
Standard E dimensions (1) or higher	4.5	5	5.5	8
Standard E dimensions (1) below	14.5	17.5	25.5	38
Maximum length	1 000	1 500	1 520	1 560

Item \ Identification number	LWLF18···BCS	LWLF24···BCS	LWLF30···BCS	LWLF42···BCS
Standard length L (n)	90 (3) 180 (6) 240 (8) 300 (10) 420 (14) 510 (17) 600 (20)	120 (3) 240 (6) 320 (8) 400 (10) 600 (15) 720 (18) 800 (20)	160 (4) 320 (8) 440 (11) 560 (14) 680 (17) 800 (20) 920 (23)	160 (4) 320 (8) 440 (11) 560 (14) 680 (17) 800 (20) 920 (23)
Pitch of mounting holes F	30	40	40	40
E	15	20	20	20
Standard E dimensions (1) or higher	5.5	6.5	6.5	6.5
Standard E dimensions (1) below	20.5	26.5	26.5	26.5
Maximum length	1 500	1 520	1 600	1 600

Note (1) Not applicable to track rail with stopper pins (supplemental code "/S").

Remarks 1. A typical identification number is indicated, but is applied to all models of the same size.
2. If not directed, E dimensions for both ends will be the same within the range of standard E dimensions. To change the dimensions, indicate the specified rail mounting hole positions "/E" of special specification. For more information, see page Ⅲ−30.

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

8 Preload amount

Clearance	: T_0	Specify this item for an assembled set or a single slide unit.
Standard	: No symbol	For details of the preload amount, see Table 4.
Light preload	: T_1	For applicable preload types, see Table 5.1 and Table 5.2.

Table 4 Preload amount

Item / Preload type	Preload symbol	Preload amount N	Operational conditions
Clearance	T_0	0 (1)	· Very light motion
Standard	(No symbol)	0 (2)	· Light and precise motion
Light preload	T_1	0.02 C_0	· Almost no vibrations · Load is evenly balanced · Light and precise motion

Notes (1) There is zero or subtle clearance.
(2) Indicates zero or minimal amount of preload.
Remark: C_0 indicates the basic static load rating.

Table 5.1 Application of preload (Standard type)

Size	Preload type (preload symbol)		
	Clearance (T_0)	Standard (No symbol)	Light preload (T_1)
1	○	–	–
2	○	–	–
3	○	–	–
5	○	○	–
7	○(1)	○	○(1)
9	○(1)	○	○(1)
12	○(1)	○	○(1)
15	○(1)	○	○(1)
20	○	○	○
25	○	○	○

Note (1) Not applicable when /HB is specified.
Remark: The mark ▭ indicates that interchangeable specification products are available.

Table 5.2 Application of preload (Wide type)

Size	Preload type (preload symbol)		
	Clearance (T_0)	Standard (No symbol)	Light preload (T_1)
2	○	–	–
4	○	–	–
6	○	–	–
10	○	○	–
14	○	○	○
18	○	○	○
24	○	○	○
30	○	○	○
42	○	○	○

Remark: The mark ▭ indicates that interchangeable specification products are available.

9 Accuracy class

High	: H	For interchangeable specification products, assemble a slide unit and a track rail of the same accuracy class.
Precision	: P	Size 1 series have "No symbols."
		For the details of accuracy class, see Table 6.1 and 6.2.

Table 6.1 Tolerance and allowable values (Series of size 1)



unit: mm

Item	Tolerance
Dim. H tolerance	±0.020
Dim. N_1 and Dim. N_2 tolerance	±0.025

Table 6.2 Tolerance and allowance (Series of size 2 or larger excluding LWLF2)



unit: mm

Item / Class (classification symbol)	High (H)	Precision (P)
Dim. H tolerance	±0.020	±0.010
Dim. N tolerance	±0.025	±0.015
Dim. variation of H (1)	0.015	0.007
Dim. variation of N (1)	0.020	0.010
Dim. variation of H for multiple assembled sets (2)	0.030	0.020
Parallelism in operation of the slide unit C surface to A surface	See Fig. 1	
Parallelism in operation of the slide unit D surface to B surface	See Fig. 1	

Notes (1) It means the size variation between slide units mounted on the same track rail.
(2) Applicable to the interchangeable specification.

Table 6.3 Tolerance and allowance (LWLF 2)

unit: mm

Item / Class (classification symbol)	High (H)	Precision (P)
Dim. H tolerance	±0.020	±0.010
Dim. N_1 and Dim. N_2 tolerance	±0.025	±0.015
Dim. variation of H (1)	0.015	0.007
Dim. variation of N (1)	0.020	0.010
Parallelism in operation of the slide unit C surface to A surface	See Fig. 1 (If the track rail length is less than 60mm, the value will be the same as 60mm.)	
Parallelism in operation of the slide unit D surface to B surface	See Fig. 1 (If the track rail length is less than 60mm, the value will be the same as 60mm.)	

Note (1) It means the size variation between slide units mounted on the same track rail.



Fig. 1 Parallelism in operation (Series of size 2 or higher)

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

10 Interchangeable

S1 specification	: S1	This is specified for the interchangeable specifications. Assemble a track rail and a slide unit with the same interchangeable code. When using in combination with different interchangeable codes, please contact IKO. Note that the combination of interchangeable codes will not have any effect on accuracy. For applicable models and sizes, see Table 2.1 and Table 2.2. "No symbol" is indicated for non-interchangeable specification.
S2 specification	: S2	
Non-interchangeable specification	: No symbol	

11 Special specification

/A, /BS, /D, /E, /HB, /I, /LR, /MN, /N, /Q, /RE, /S, /U, /W○, /Y○

For applicable special specifications, see Tables 7.1, 7.2, 7.3, and 7.4.
For combination of multiple special specifications, see Table 8.
For details of special specification, see page Ⅲ−29.

Table 7.1 Application of special specifications (Interchangeable specification, single slide unit)

Special specification	Supplemental code	Size									
		1	2	3	5	7	9	12	15	20	25
		–	4	6	10	14	18	24	30	42	–
No end seal	/N	–	–	–	○	○	○	○	○	○	○
With C-Lube plate (1)	/Q	–	–	–	○	○	○	○	○	○	○
Under seal	/U	–	–	–	×	×	○	○	○	○	○

Note (1) Applicable to LWL(F) series.

Table 7.2 Application of special specifications (Interchangeable specification, single track rail)

Special specification	Supplemental code	Size									
		1	2	3	5	7	9	12	15	20	25
		–	4	6	10	14	18	24	30	42	–
Specified rail mounting hole positions	/E	–	–	–	○	○	○	○	○	○	○
Without track rail mounting bolt	/MN	–	–	–	○	○	○	○	○	○	○

Table 7.3 Application of special specifications (Interchangeable specification, assembled set)

Special specification	Supplemental code	Size									
		1	2	3	5	7	9	12	15	20	25
		–	4	6	10	14	18	24	30	42	–
Opposite reference surfaces arrangement	/D	–	–	–	○	○	○	○	○	○	○
Specified rail mounting hole positions	/E	–	–	–	○	○	○	○	○	○	○
Without track rail mounting bolt (1)	/MN	–	–	–	○	○	○	○	○	○	○
No end seal	/N	–	–	–	○	○	○	○	○	○	○
With C-Lube plate (2)	/Q	–	–	–	○	○	○	○	○	○	○
Under seal	/U	–	–	–	×	×	○	○	○	○	○

Notes (1) Not applicable to tapped rail specification.
(2) Applicable to LWL(F) series.

Table 7.4 Application of special specifications (Non-interchangeable specification, standard type)

Special specification	Supplemental code	Size									
		1	2	3	5	7	9	12	15	20	25
Butt-jointing track rails (1) (2)	/A	×	×	×	○	○	○	○	○	○	○
Stainless steel end plate (3)	/BS	×	○	○	○	○	○	○	○	○	×
Opposite reference surfaces arrangement	/D	×	○	○	○	○	○	○	○	○	○
Specified rail mounting hole positions	/E	×	○	○	○	○	○	○	○	○	○
Hybrid C-Lube Linear Way (4)	/HB	×	×	×	×	○	○	○	○	×	×
Inspection sheet	/I	×	○	○	○	○	○	○	○	○	○
Black chrome surface treatment (track rail) (2)	/LR	×	×	×	×	○	○	○	○	○	○
Without track rail mounting bolt (2)	/MN	×	×	×	○	○	○	○	○	○	○
No end seal	/N	×	×	×	○	○	○	○	○	○	○
With C-Lube plate (3)	/Q	×	×	×	○	○	○	○	○	○	○
Special environment seal (3)	/RE	×	×	×	○	○	○	○	○	○	×
Track rail with stopper pins	/S	×	×	×	○	○	○	○	○	○	○
Under seal	/U	×	×	×	×	×	○	○	○	○	○
A group of multiple assembled sets	/W○	×	○	○	○	○	○	○	○	○	○
Specified grease (5)	/Y○	×	○(6)	○	○	○	○	○	○	○	○

Notes (1) Not applicable to high carbon steel made products.
(2) Not applicable to tapped rail specification.
(3) Applicable to LWL series.
(4) Applicable only to ML.
(5) ML series is applicable only to /YCG.
(6) Applicable only to /YNG.

Table 7.5 Application of special specifications (Non-interchangeable specification, wide type)

Special specification	Supplemental code	Size								
		2	4	6	10	14	18	24	30	42
Butt-jointing track rails (1) (2)	/A	×	×	×	○	○	○	○	○	○
Stainless steel end plate (3)	/BS	×	×	×	○	○	○	○	○	○
Opposite reference surfaces arrangement	/D	×	○	○	○	○	○	○	○	○
Specified rail mounting hole positions	/E	○	○	○	○	○	○	○	○	○
Inspection sheet	/I	○	○	○	○	○	○	○	○	○
Black chrome surface treatment (track rail) (2)	/LR	×	×	×	×	○	○	○	○	○
Without track rail mounting bolt (2)	/MN	×	○	○	○	○	○	○	○	○
No end seal	/N	×	×	×	○	○	○	○	○	○
With C-Lube plate (3)	/Q	×	×	×	○	○	○	○	○	○
Special environment seal (3)	/RE	×	×	×	○	○	○	○	○	○
Track rail with stopper pins	/S	×	×	×	○	○	○	○	○	○
Under seal	/U	×	×	×	×	×	○	○	○	○
A group of multiple assembled sets	/W○	○	○	○	○	○	○	○	○	○
Specified grease (4)	/Y○	×	○(5)	○	○	○	○	○	○	○

Notes (1) Not applicable to high carbon steel made products.
(2) Not applicable to tapped rail specification.
(3) Applicable to LWLF series.
(4) MLF series is applicable only to /YCG.
(5) Applicable only to /YNG.

Table 8 Combination of supplemental codes

	A	BS	D	E	HB	I	LR	MN	N	Q	RE	S	U	W
BS	○													
D	○	○												
E	–	○	–											
HB	○	–	○	○										
I	○	○	○	○	○									
LR	–	○	○	○	○	○								
MN	○	○	○	○	○	○	○							
N	○	○	○	○	○	○	○	○						
Q	○	○	○	○	–	○	○	○	○					
RE	○	○	○	○	–	○	○	○	–	○				
S	○	○	○	○	○	○	○	○	○	○	○			
U	○	○	○	○	○	○	○	○	–	○	–	○		
W	○	○	○	–	○	○	○	○	○	○	○	○	○	
Y	○	○	○	○	○(1)	○	○	○	○	–	○	○	○	○

Note (1) Applicable only to YCG (Low Dust-Generation Grease for Clean Environment CG2).
Remarks 1. The combination of "−" shown in the table is not available.
2. When using multiple types for combination, please indicate by arranging the symbols in alphabetical order.

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Table 9 Dimension of slide unit with C-Lube plate (Supplemental code /Q)



unit: mm

Identification number	L_1	L_4	Identification number	L_1	L_4
LWLC 5···B	22	–	LWLFC 10···B	26.5	–
LWL 5···B	25	–	LWLF 10···B	30.5	–
LWLC 7···B	27	–	LWLFC 14···B	30.5	–
LWL 7···B	31.5	–	LWLF 14···B	39.5	–
LWLG 7···B	39	–	LWLFG 14···B	50	–
LWLC 9···B	30	–	LWLFC 18···B	34.5	–
LWL 9···B	39	–	LWLF 18···B	46.5	–
LWLG 9···B	49	–	LWLFG 18···B	58.5	–
LWLC 12···B	33	–	LWLFC 24···B	38.5	–
LWL 12···B	42	–	LWLF 24···B	52	–
LWLG 12···B	52	–	LWLFG 24···B	67	–
LWLC 15···B	42	47	LWLFC 30···B	45.5	50
LWL 15···B	52	57	LWLF 30···B	59.5	64
LWLG 15···B	67	72	LWLFG 30···B	78.5	83
LWLC 20···B	48	53	LWLFC 42···B	51.5	56
LWL 20···B	60	65	LWLF 42···B	65	70
LWLG 20···B	78	83	LWLFG 42···B	84.5	89
LWLC 25···B	63.5	74			
LWL 25···B	87.5	98			
LWLG 25···B	107.5	117			

Remarks 1. The dimensions of the slide unit with C-Lube at both ends are indicated.
2. A typical identification number is indicated, but is applied to all LWL(F) series models of the same size.

Table 10 Load rating / static moment rating of Hybrid C-Lube Linear Way (Supplemental code /HB)

Identification number	C N	C_0 N	T_0 N·m	T_x(1) N·m	T_Y(1) N·m
MLC 7···/HB	937	965	3.5	1.6 12.6	1.3 10.6
ML 7···/HB	1 330	1 610	5.9	4.0 23.9	3.3 20.1
MLG 7···/HB	1 690	2 250	8.2	7.5 43.1	6.3 36.2
MLC 9···/HB	1 180	1 260	5.9	2.4 18.2	2.1 15.3
ML 9···/HB	1 810	2 340	10.9	7.7 43.4	6.5 36.4
MLG 9···/HB	2 370	3 420	15.9	15.9 83.6	13.4 70.1
MLL 9···/HB	2 870	4 500	20.9	27.1 134	22.7 112
MLC 12···/HB	2 210	2 030	12.6	4.5 35.5	3.8 29.8
ML 12···/HB	3 330	3 650	22.6	13.1 79.2	11.0 66.4
MLG 12···/HB	4 310	5 270	32.7	26.0 143	21.9 120
MLL 12···/HB	5 820	8 110	50.3	59.3 288	49.8 242
MLC 15···/HB	3 490	3 310	25.5	9.9 71.8	8.3 60.3
ML 15···/HB	4 980	5 520	42.5	25.3 146	21.2 122
MLG 15···/HB	6 620	8 280	63.7	54.3 288	45.5 241
MLL 15···/HB	8 370	11 600	89.2	104 497	86.9 417

Note (1) The upper values of T_x and T_y are for one slide unit and the lower values are for two slide units in close contact.

Table 11 Dimension of track rail with stopper pins (Supplemental code /S)



unit: mm

Size		a	b	c
5	–	2	2	1.6
7	–	2.5	2.5	2
9	–		3	
–	10		2	1.6
12	–		3	2
–	14			
15	–		4	
–	18		3	
20	–		5	
–	24		3	
25	–	3.5	5	
–	30	2.5	4	
–	42		5	

Table 12 H_1 dimension with under seal (Supplemental code /U)



unit: mm

Size		H_1
9	–	1
12	–	2
15	–	3
–	18	2
20	–	4
–	24	2
25	–	5(1)
–	30	2
–	42	3

Note (1) The dimensions are the same as those before mounting of under seal.

Lubrication

Lithium-soap base grease (MULTEMP PS No.2 [KYODO YUSHI CO., LTD.]) is pre-packed in ML(F) and LWL(F) series. Additionally, ML(F) series has C-Lube placed in the recirculation part of balls, so that the interval for reapplicating lubricant can be extended and maintenance works such as grease job can be reduced significantly.
ML(F) series and LWL(F) series have grease nipple or oil hole as indicated in Table 14. Since the Size 1, 2, 3, 4 and 6 series do not have an oil hole, apply grease directly to the raceway part of the track rail for re-greasing. Supply nozzles fit to each shapes of grease nipple and dedicated supplying equipment (miniature greasers) fit to oil holes are also available. For order of these parts for lubrication, see Table 13 and Table 14.1 on Page Ⅲ−23, and Table 15 on page Ⅲ−24.

Table 13 Oil hole specifications



unit: mm

Size		d_1	d_2
5	10	0.5	1.1
7	14		1.2
9	18		1.5
12	24		2

Dust Protection

The slide units of ML(F) series and LWL(F) series are equipped with end seals as standard for dust protection. However, if large amount of contaminant or dust are floating, or if large particles of foreign substances such as chips or sand may adhere to the track rail, it is recommended to attach a protective cover to the linear motion mechanism.
No end seal is provided for size 1, 2, 3, 4 or 6 series. For applications in the environment not clean enough, cover the entire unit with a protective case, etc. to prevent harmful foreign substances such as dust and particles from outside to enter.

Table 14 Parts for lubrication

Size		Grease nipple type (1)	Applicable supply nozzle type	Bolt size of female threads for piping
5, 7, 9, 12	10, 14, 18, 24	Oil hole	Miniature greaser MG10B/MT2	–
15, 20	30, 42	A-M3	A-5120V A-5240V B-5120V B-5240V	
25	–	B-M4	A-8120V B-8120V	M4

Note (1) For grease nipple specification, see Table 14.1 on page Ⅲ−23.
Remark: Stainless steel grease nipple is also available. If needed, please contact IKO.

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Precaution for Use

❶ Mounting surface, reference mounting surface and general mounting structure

When mounting the ML(F) series and LWL(F) series, properly align the reference mounting surfaces B and D (D1 or D2)of the track rail and slide unit with the reference mounting surface of the table and bed and fix them. (See Fig. 2)

Reference mounting surfaces B and D (D1 or D2) and mounting surfaces A and C are precisely ground. By machining the mounting surface of the mating member, such as machine or device, to high accuracy and mounting them properly, stable linear motion with high accuracy is obtained.

The LWL1···Y track rail has the mounting structure in the lateral direction. Two types of mounting structures are available (as shown in Fig. 3.1 and Fig. 3.2).

The reference mounting surfaces of the slide unit LWL1 (Y) and LWLF2 are located at both the left and right sides (D1 and D2). (See Fig. 5.1)

Excluding LWL1 (Y) and LWLF2, the reference mounting surface of the slide unit is on the opposite side of the IKO mark. (See Fig. 5.2)

The reference mounting surface of the track rail, with the exception of LWL1 (Y), is identified by locating the IKO mark on the top surface of the track rail. It is the side surface above the mark (in the direction of the arrow). (See Fig. 5.1 and Fig. 5.2)



Fig. 2 Reference mounting surface and typical mounting structure



Fig. 3.1 Reference mounting surface of LWL1···Y and typical mounting structure ①



Fig. 3.2 Reference mounting surface of LWL1···Y and typical mounting structure ②



Fig. 4 Reference mounting surface of size 2, 3, 4 and 6 series and typical mounting structure



Fig. 5.1 Reference mounting surface of LWL1 (Y) and LWLF2



Fig. 5.2 Reference mounting surface of products other than LWL1 (Y) and LWLF2

❷ Mounting screws for slide unit

To mount a slide unit, tightly fasten the bolt against female thread of slide unit.

The female thread is created through holes of the slide unit for size 1 series, and also through holes for the slide unit and track rail for size 2, 3, 4 and 6 series. When the fixing thread depth of the mounting screw goes too deep, it can interfere with the track rail and impact the running accuracy or product life so that the fixing thread depth should be within the screwing depth specified in the dimension table.

Also prepare the small screws dedicated to precision devices (head diameter 1.8 mm or smaller) for the mounting bolt of slide unit of size 1 and LWLF2.

❸ Mounting screws for track rail

In the size 2 and 3 series and tapped rail specifications, track rail mounting bolts are not appended. Prepare mounting bolts whose fixing thread depth is less than H_4 in dimension table.

❹ Shoulder height and corner radius of the reference mounting surface

For the opposite corner of the mating reference mounting, it is recommended to have relieved fillet as indicated in Fig. 6 Recommended value for the shoulder height on the mating side is indicated in Table 16.



Fig. 6 Corner of the mating reference mounting

❺ Tightening torque for fixing screw

Typical tightening torque for mounting ML(F) series and LWL(F) series to the steel mating member material is indicated in Table 15. When vibration and shock of the machine or device are large, fluctuating load is large, or moment load is applied, fix it by using the torque 1.2 to 1.5 times larger than the value indicated in the table as necessary. If the mating member material is cast iron or aluminum alloy, reduce the tightening torque depending on the strength characteristics of the mating member material.

Table 15 Tightening torque for fixing screw

Bolt size	Tightening torque N · m	
	Stainless steel-made screw	High carbon steel-made screw
M1 ×0.25	0.04	–
M1.4×0.3	0.10	–
M1.6×0.35	0.15	–
M2 ×0.4	0.31	–
M2.5×0.45	0.62	–
M3 ×0.5	1.1	1.3
M4 ×0.7	2.5	2.9
M5 ×0.8	5.0	5.7
M6 ×1	8.5	–

Remarks 1. The tightening torque is calculated based on strength division 8.8 and property division A2-70.
2. It is recommended that the tightening torque of slide unit mounting holes for series size 1 is to be 70 to 80 % of the values in the table.
3. For the tightening torque of cross-recessed pan head screws for precision equipment, see Table 22 on page III-38.

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Table 16 Shoulder height and corner radius of the reference mounting surface



Mounting part of slide unit　　Mounting part of track rail

unit: mm

Identification number		Mounting part of slide unit		Mounting part of track rail	
		Shoulder height h_1	Corner radius R_1 (Maximum)	Shoulder height (1) h_2	Corner radius R_2 (Maximum)
–	LWL 1···Y	1.3	–	2	–
–	LWL 1			–	
–	LWL 2	1	0.1	0.5	0.05
ML 3	LWL 3	1.2	0.15	0.8	0.1
ML 5	LWL 5···B	2	0.3	0.8	0.2
ML 7	LWL 7···B	2.5	0.2	1.2	0.2
ML 9	LWL 9···B	3	0.2	1.5	0.2
–	LWL 9···BCS		0.4		
ML 12	LWL 12···B	4	0.2	2.5	0.2
–	LWL 12···BCS		0.4		
ML 15	LWL 15···B	4.5	0.2	3	0.2
–	LWL 15···BCS		0.4		
ML 20	LWL 20···B	5	0.2	4	0.2
–	LWL 20···BCS		0.4		
ML 25	LWL 25···B	6.5	0.7	4	0.7
–	LWLF 2	1.3	–	–	–
–	LWLF 4	1.5	0.1	0.8	0.1
MLF 6	LWLF 6	2	0.1	0.8	0.1
MLF 10	LWLF 10···B	2	0.3	1.2	0.2
MLF 14	LWLF 14···B	2.5	0.2	1.2	0.2
MLF 18	LWLF 18···B	3	0.2	2.5	0.2
–	LWLF 18···BCS		0.4		
MLF 24	LWLF 24···B	4	0.2	2.5	0.2
–	LWLF 24···BCS		0.4		
MLF 30	LWLF 30···B	4.5	0.2	2.5	0.2
–	LWLF 30···BCS		0.4		
MLF 42	LWLF 42···B	5	0.2	3	0.2
–	LWLF 42···BCS		0.4		

Note (1) For models with under seals (supplemental code "/U"), it is recommended to use the values 1mm smaller than the values in the table. However for the models of size 9 with under seal, 0.8 mm is recommended.

Remark: A typical identification number is indicated, but is applied to all models of the same size.

Track rail mounting bolts for slide unit and tapped rail specification

For LWL(F) series, track rail mounting bolts for slide unit and tapped rail specification shown in Table 17 and Table 18 are available. If these parts are necessary, please contact IKO. Note that the dimensions are different from those of the appended track rail mounting bolts listed on pages II-24 to II-38.

Table 17 Cross-recessed pan head screw for precision equipment



unit: mm

Bolt size (d)	Pitch of screw P	d_k	k	l
M1	0.25	1.8	0.45	3, 4, 5
M1.4 (1)	0.3	2.5	0.8	2.5, 3, 4
M1.6	0.35	2.8	0.85	4, 5, 6
M2 (1)	0.4	3.5	1	3, 4, 5

Note (1) Based on Camera & Imaging Products Association CIPA AD-003-2020 cross recessed head screw for precision equipment (No. 0 small screw). The type is Class 3.

Table 18 Hexagon socket head bolt



unit: mm

Bolt size (d)	Pitch of screw P	d_k	k	s	t	l
M1.4	0.3	2.6	1.4	1.3	0.6	2.5, 3, 4
M1.6 (1)	0.35	3	1.6	1.5	0.7	4, 5, 6
M2 (1)	0.4	3.8	2	1.5	1	3, 4, 5

Note (1) Based on hexagon socket head bolts equivalent to JIS B 1176.

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

IKO C-Lube Linear Way ML

Standard type					
Shape	ML • LWL				
Size	1	2	3	5	7
	9	12	15	20	25





Identification number		Interchangeable	Mass (Ref.) g		Dimensions of assembly mm			Dimensions of slide unit mm							Dimensions of track rail mm							Mounting bolt for track rail (2) mm	Basic dynamic load rating (3)	Basic static load rating (5)	Static moment rating (5)		
ML series	LWL series (No C-Lube)		Slide unit	Track rail (per 100 mm)	H	H_1	N	W_2	L_1	L_2	L_3	M_1×depth	H_2		W	H_4	H_5	M_2	d_3	E	F	Bolt size× ℓ	C	C_0	T_0	T_X	T_Y
																							N	N	N·m	N·m	N·m
–	LWL 1···Y	–	0.16	2.1	4.2	2.2	1.5	4	6.5	2	3.9	M1 ×0.9	1.2		1	3.1	1.1	M1.4 Through	1.1	3	6	Cross-recessed pan head screw for precision equipment (Class 1) M1× ℓ or M1.4× ℓ (3)	66.8	113	0.06	0.07 0.47	0.09 0.56
–	LWL 1	–		1.0	2.5	0.5										1.4	–	–	–	–	–	–					
–	LWL 2	–	0.9	2.8	3.2	0.7	2	6	12.5	4	8.8	M1.4×1.1	–		2	2	–	M1 Through	–	4	8	Cross-recessed pan head screw for precision equipment (Class 1) M1 × ℓ (4)	211	381	0.42	0.54 2.9	0.64 3.5
MLC 3		–	0.9	5.3	4	1	2.5	8	10.5	3.5	7	M1.6×1.3	–		3	2.6	–	M1.6 Through	–	5	10	Cross-recessed pan head screw for precision equipment M1.6× ℓ (4)	272	406	0.65	0.49 2.7	0.58 3.2
	LWLC 3	–	1.0						11.5		6.7												251	361	0.58	0.39 2.7	0.47 3.2
ML 3		–	1.3						14.5	5.5	11	M2 ×1.3											371	632	1.0	1.1 5.6	1.3 6.6
	LWL 3	–	1.6						15.5		10.7												353	587	0.94	0.98 5.6	1.2 6.7

Notes (1) Track rail lengths L are shown in Table 3.1 on page Ⅱ−10.
(2) Track rail mounting bolts are not appended.
(3) Prepare screws according to mounting structure.
(4) Choose screws whose dimension allow fixing thread depth into track rail ℓ to be less than H_4.
(5) The direction of basic dynamic load rating (C), basic static load rating (C_0), and static moment rating (T_0, T_X, T_Y) are shown in the sketches below.
The upper values of T_X and T_Y are for one slide unit and the lower values are for two slide units in close contact.

Remarks 1. Metal parts are made of stainless steel.
2. Do not disassemble a slide unit from the track rail because steel balls are not retained. No end seal is attached.
3. The specification of small size mounting bolts (M2 and less) are show on page Ⅱ−22. If needed, please contact IKO.



Example of identification number of assembled set

Model code		Dimensions	Part code		Model code	Preload symbol	Classification symbol	Supplemental code
LWL		2	C2	R80		T0	P	/D
①	②	③	④	⑤	①	⑥	⑦	⑧

① Model

ML	Standard type
LWL	
LWL···Y	

② Length of slide unit

C	Short
No symbol	Standard

③ Size: 1, 2, 3

④ Number of slide unit (2)

⑤ Length of track rail (80 mm)

⑥ Preload amount

T0	Clearance

⑦ Accuracy class

No symbol	Ordinary
H	High
P	Precision

⑧ Special specification: BS, D, E, I , W, Y

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Standard type

Shape: **ML • LWL**



Size	1	2	3	5	7
	9	12	15	20	25





Tapped rail specification
LWL···N



Identification number		Interchangeable	Mass (Ref.) g		Dimensions of assembly mm			Dimensions of slide unit mm								Dimensions of track rail mm						Appended mounting bolt for track rail (2) mm	Basic dynamic load rating (4)	Basic static load rating (4)	Static moment rating (4)		
ML series	LWL series (No C-Lube)		Slide unit	Track rail (per 100 mm)	H	H_1	N	W_2	W_3	W_4	L_1	L_2	L_3	M_1×depth	H_3	W	H_4	M_2	d_3	d_4	h	E	F	Bolt size× ℓ	C N	C_0 N	T_0 N·m	T_X N·m	T_Y N·m
MLC 5	LWLC 5···B	○	3.4	12	6	1	3.5	12	8	2	16	–	9.6	M2×1.5	1.2	5	3.7	–	2.4	3.6	0.8	7.5	15	Cross-recessed pan head screw for precision equipment (Class 1) M2×6	562	841	2.2	1.4 8.5	1.2 7.2
MLC 5···N*	LWLC 5···N*	–		13														M2.5 Through	–	–	–			M2.5× ℓ (3) (Not appended)					
ML 5		○	4.3	12							19		12.6					–	2.4	3.6	0.8			Cross-recessed pan head screw for precision equipment (Class 1) M2×6	676	1 090	2.9	2.3 12.8	1.9 10.8
	LWL 5···B	○	4.4																									
ML 5···N*		–	4.3	13														M2.5 Through	–	–	–			M2.5× ℓ (3) (Not appended)					
	LWL 5···N*	–	4.4																									
MLC 7		○	6.7	22	8	1.5	5	17	12	2.5	19	–	9.6	M2×2.5	1.5	7	5	–	2.4	4.2	2.3	7.5	15	Hexagon socket head bolt M2×6	937	1 140	4.1	1.8 14.9	1.5 12.5
	LWLC 7···B	○	7.1																									
MLC 7···N*		–	6.7	24														M3 Through	–	–	–			M3× ℓ (3) (Not appended)					
	LWLC 7···N*	–	7.1																									
ML 7		○	9.1	22							23.5	8	14.3					–	2.4	4.2	2.3			Hexagon socket head bolt M2×6	1 330	1 890	6.9	4.7 28.2	3.9 23.6
	LWL 7···B	○	10																									
ML 7···N*		–	9.1	24														M3 Through	–	–	–			M3× ℓ (3) (Not appended)					
	LWL 7···N*	–	10																									
MLG 7		○	13	22							31	12	21.6					–	2.4	4.2	2.3			Hexagon socket head bolt M2×6	1 690	2 650	9.7	8.8 50.7	7.4 42.5
	LWLG 7···B	○	14																									
MLG 7···N*		–	13	24														M3 Through	–	–	–			M3× ℓ (3) (Not appended)					
	LWLG 7···N*	–	14																									

Notes (1) Track rail lengths L are shown in Table 3.1 on page Ⅱ−10.
(2) The appended mounting bolts are hexagon socket head bolts equivalent to JIS B 1176 or CIPA AD-003-2020 cross recessed head screw for precision equipment (No. 0 small screw).
(3) Choose screws whose dimension allow fixing thread depth into track rail ℓ to be less than H_4.
(4) The direction of basic dynamic load rating (C), basic static load rating (C_0), and static moment rating (T_0, T_X, T_Y) are shown in the sketches below.
The upper values of T_X and T_Y are for one slide unit and the lower values are for two slide units in close contact.
If hybrid C-Lube Linear Way specification (supplemental code "/HB") is selected in MLC7, ML7, and MLG7, see Table 10 on page Ⅱ−17.

Remarks 1. The specification of oil hole is shown in Table 13 on page Ⅱ−18.
2. The identification numbers with * are our semi-standard items.



Example of identification number of assembled set

Model code	Dimensions	Part code			Model code	Preload symbol	Classification symbol	Interchangeable code	Supplemental code
ML	C	7	C2	R120		T1	P		/D
①	②	③	④	⑤	①	⑥	⑦	⑧	⑨

① Model

ML	Standard type
LWL···B	
LWL···N	

② Length of slide unit

C	Short
No symbol	Standard
G	Long

③ Size: 5, 7

④ Number of slide unit (2)

⑤ Length of track rail (120 mm)

⑥ Preload amount

T0	Clearance
No symbol	Standard
T1	Light preload

⑦ Accuracy class

H	High
P	Precision

⑧ Interchangeable

No symbol	Non-interchangeable specification
S1	S1 specification
S2	S2 specification

⑨ Special specification: A, BS, D, E, HB, Ⅰ, LR, MN, N, Q, RE, S, W, Y

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

IKO C-Lube Linear Way ML

Standard type

Shape	ML • LWL
Size	1 · 2 · 3 · 5 · 7
	9 · 12 · 15 · 20 · 25





Tapped rail specification
LWL···N



Identification number		Interchangeable	Mass (Ref.) g		Dimensions of assembly mm			Dimensions of slide unit mm								Dimensions of track rail mm								Appended mounting bolt for track rail (2) mm	Basic dynamic load rating (4)	Basic static load rating (4)	Static moment rating (4)		
ML series	LWL series (No C-Lube)		Slide unit	Track rail (per 100 mm)	H	H_1	N	W_2	W_3	W_4	L_1	L_2	L_3	M_1×depth	H_3	W	H_4	M_2	d_3	d_4	h	E	F	Bolt size× ℓ	C N	C_0 N	T_0 N·m	T_X N·m	T_Y N·m
MLC 9	LWLC 9···B	○	11	35	10	2	5.5	20	15	2.5	21.5	–	11.9	M3×3	2.2	9	6	–	3.5	6	3.5	10	20	M3×8	1 180	1 480	6.9	2.9 21.4	2.4 18.0
MLC 9···N*	LWLC 9···N*	–	11	37														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
ML 9		○	18	35							30	10	20.8					–	3.5	6	3.5			M3×8	1 810	2 760	12.8	9.1 51.1	7.6 42.9
	LWL 9···B	○	19																									
–	LWL 9···BCS	○																										
ML 9···N*		–	18	37														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
	LWL 9···N*	–	19																									
MLG 9		○	26	35							40.5	15	30.9					–	3.5	6	3.5			M3×8	2 370	4 030	18.7	18.7 98.3	15.7 82.5
	LWLG 9···B	○	28																									
MLG 9···N*		–	26	37														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
	LWLG 9···N*	–	28																									
MLL 9	–	○	34	35							50	26	40.4					–	3.5	6	3.5			M3×8	2 870	5 300	24.6	31.9 157	26.7 132
MLL 9···N*	–	–		37														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
MLC 12	LWLC 12···B	○	22	65	13	3	7.5	27	20	3.5	25	–	13	M3×3.5	2.7	12	8	–	3.5	6.5	4.5	12.5	25	M3×8	2 210	2 380	14.8	5.3 41.7	4.5 35.0
ML 12		○	34								34	15	21.6												3 330	4 290	26.6	15.4 93.1	12.9 78.2
	LWL 12···B	○	35																									
–	LWL 12···BCS	○																										
MLG 12		○	48								44	20	32												4 310	6 200	38.4	30.6 168	25.7 141
	LWLG 12···B	○	51																									
MLL 12	–	○	70								59.5	30	47.3												5 820	9 540	59.1	69.8 339	58.6 285

Notes (1) Track rail lengths L are shown in Table 3.1 on page Ⅱ−10 and Table 3.3 on page Ⅱ−12.
(2) The appended track rail mounting bolts are hexagon socket head bolts equivalent to JIS B 1176. For stainless steel model, stainless steel bolts are appended.
(3) Choose screws whose dimension allow fixing thread depth into track rail ℓ to be less than H_4.
(4) The direction of basic dynamic load rating (C), basic static load rating (C_0), and static moment rating (T_0, T_X, T_Y) are shown in the sketches below.
The upper values of T_X and T_Y are for one slide unit and the lower values are for two slide units in close contact.
If hybrid C-Lube Linear Way specification (supplemental code "/HB") is selected in ML series, see Table 10 on page Ⅱ−17.

Remarks 1. The specification of oil hole is shown in Table 13 on page Ⅱ−18.
2. The identification numbers with * are our semi-standard items.



Example of identification number of assembled set

Model code	Dimensions	Part code	Model code	Material code	Preload symbol	Classification symbol	Interchangeable code	Supplemental code
ML	G	9	C2	R160			T1	P		/D
①	②	③	④	⑤	①	⑥	⑦	⑧	⑨	⑩

① Model

ML	Standard type
LWL···B	
LWL···N	

② Length of slide unit

C	Short
No symbol	Standard
G	Long
L	Extra high rigidity long

③ Size: 9, 12

④ Number of slide unit (2)

⑤ Length of track rail (160 mm)

⑥ Material type

No symbol	Stainless steel made
CS	High carbon steel made

⑦ Preload amount

T0	Clearance
No symbol	Standard
T1	Light preload

⑧ Accuracy class

H	High
P	Precision

⑨ Interchangeable

No symbol	Non-interchangeable specification
S1	S1 specification
S2	S2 specification

⑩ Special specification: A, BS, D, E, HB, Ⅰ, LR, MN N, Q, RE, S, U, W, Y

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

IKO C-Lube Linear Way ML

Standard type

Shape: **ML • LWL**



Size	1	2	3	5	7
	9	12	15	20	25





Identification number		Interchangeable	Mass (Ref.) g		Dimensions of assembly mm			Dimensions of slide unit mm									Dimensions of track rail mm							Appended mounting bolt for track rail (2) mm	Basic dynamic load rating (3)	Basic static load rating (3)	Static moment rating (3)		
ML series	LWL series (No C-Lube)		Slide unit	Track rail (per 100 mm)	H	H_1	N	W_2	W_3	W_4	L_1	L_2	L_3	L_4	M_1×depth	H_3	W	H_4	d_3	d_4	h	E	F	Bolt size× ℓ	C N	C_0 N	T_0 N·m	T_X N·m	T_Y N·m
MLC 15		○	43	107	16	4	8.5	32	25	3.5	32	–	17.8	37	M3×4	3.1	15	10	3.5	6.5	4.5	20	40	M3×10	3 490	3 890	30.0	11.7 84.5	9.8 70.9
	LWLC 15···B	○	42										17.7															
ML 15		○	63								42	20	27.9	47											4 980	6 490	50.0	29.7 172	24.9 144
	LWL 15···B	○	64										27.8															
–	LWL 15···BCS	○																										
MLG 15		○	93								57	25	42.8	62											6 620	9 740	75.0	63.9 338	53.6 284
	LWLG 15···B	○	95										42.7															
MLL 15	–	○	122								72	40	57.7	76											8 370	13 600	105	122 585	102 491
MLC 20	LWLC 20···B	○	89	156	20	5	10	40	30	5	38	–	22.3	43	M4×6	4.2	20	11	6	9.5	5.5	30	60	M5×14	4 580	5 300	54.0	19.4 134	16.3 112
ML 20		○	130								50	25	34.6	55											6 650	9 080	92.6	52.7 280	44.2 235
	LWL 20···B	○	133																									
–	LWL 20···BCS	○																										
MLG 20		○	189								68	30	52.3	73											8 510	12 900	131	102 529	85.7 444
	LWLG 20···B	○	196																									
MLC 25		○	189	243	25	5	12.5	48	35	6.5	54.5	–	31.9	64	M6×7	5	23	15	7	11.0	9.0	30	60	M6×16	9 120	10 600	128	57.4 376	48.1 316
	LWLC 25···B	○	190																									
ML 25		○	305								78	35	55.7	88											13 500	18 500	223	163 887	137 744
	LWL 25···B	○	310																									
MLG 25		○	405								98	40	75.5	108											16 700	25 200	303	293 1 480	246 1 240
	LWLG 25···B	○	413																									

Notes (1) Track rail lengths L are shown in Table 3.1 on page Ⅱ−10 and Table 3.3 on page Ⅱ−12.

(2) The appended track rail mounting bolts are hexagon socket head bolts equivalent to JIS B 1176. For stainless steel model, stainless steel bolts are appended.

(3) The direction of basic dynamic load rating (C), basic static load rating (C_0), and static moment rating (T_0, T_X, T_Y) are shown in the sketches below.
The upper values of T_X and T_Y are for one slide unit and the lower values are for two slide units in close contact.
If hybrid C-Lube Linear Way specification (supplemental code "/HB") is selected in MLC15, ML15, MLG15, and MLL15, see Table 10 on page Ⅱ−17.

(4) The shapes of grease nipple vary by size. The specifications are shown in Table 14 on page Ⅱ—18.



Example of identification number of assembled set

Model code	Dimensions	Part code		Model code	Material code	Preload symbol	Classification symbol	Interchangeable code	Supplemental code
ML	G	15	C2	R320			T1	P		/D
①	②	③	④	⑤	①	⑥	⑦	⑧	⑨	⑩

① Model

ML	Standard type
LWL···B	

② Length of slide unit

C	Short
No symbol	Standard
G	Long
L	Extra high rigidity long

③ Size: 15, 20, 25

④ Number of slide unit (2)

⑤ Length of track rail (320 mm)

⑥ Material type

No symbol	Stainless steel made
CS	High carbon steel made

⑦ Preload amount

T0	Clearance
No symbol	Standard
T1	Light preload

⑧ Accuracy class

H	High
P	Precision

⑨ Interchangeable

No symbol	Non-interchangeable specification
S1	S1 specification
S2	S2 specification

⑩ Special specification: A, BS, D, E, HB, Ⅰ, LR, MN N, Q, RE, S, U, W, Y

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Wide type					
Shape	MLF • LWLF				
Size	2	4	6	10	14
	18	24	30	42	







Identification number		Interchangeable	Mass (Ref.) g		Dimensions of assembly mm			Dimensions of slide unit mm									Dimensions of track rail mm								Appended mounting bolt for track rail mm	Basic dynamic load rating (4)	Basic static load rating (4)	Static moment rating (4)		
MLF series	LWLF series (No C-Lube)		Slide unit	Track rail (per 100 mm)	H	H_1	N	W_2	W_3	W_4	L_1	L_2	L_3	M_1×depth	H_2	H_3	W	H_4	M_2	d_3	d_4	h	E	F	Bolt size× ℓ	C N	C_0 N	T_0 N·m	T_X N·m	T_Y N·m
–	LWLF 2(2)	–	0.21	2	2.5	0.5	1.5	5	–	–	6.5	2	3.9	M1 × 0.9	1.2	–	2	1.4	M1 Through	–	–	–	3	6	M1× ℓ (3) (Not appended)	66.8	113	0.12	0.07 0.47	0.09 0.56
–	LWLF 4(2)	–	2.1	6.8	4	1	3	10	–	5	17	6.5	11.9	M2 × 1.3	–	–	4	2.6	–	1.8	2.8	0.75	5	10	Cross-recessed pan head screw for precision equipment (Class 1) M1.6×5	390	677	1.4	1.3 7.1	1.5 8.4
MLFC 6(2)		–	2.1	13	4.5	1	3	12	–	6	15	4.5	9.8	M2 × 1.6	–	–	6	2.8	–	2.4	4	1.5	7.5	15	Cross-recessed pan head screw for precision equipment (Class 3) M2×4	334	542	1.7	0.84 5.1	1.0 6.1
	LWLFC 6(2)	–	2.4																										
MLFC 6···N(2)*		–	2.1	12															M3 Through	–	–	–			M3× ℓ (3) (Not appended)					
	LWLFC 6···N(2)*	–	2.4																										
MLF 6(2)		–	3.1	13							20	8	14.6						–	2.4	4	1.5			Cross-recessed pan head screw for precision equipment (Class 3) M2×4	443	813	2.5	1.8 9.9	2.2 11.8
	LWLF 6(2)	–	3.4																										
MLF 6···N(2)*		–	3.1	12															M3 Through	–	–	–			M3× ℓ (3) (Not appended)					
	LWLF 6···N(2)*	–	3.4																										

Notes (1) Track rail lengths L are shown in Table 3.2 on page Ⅱ−11.
(2) Steel balls are not retained. No end seal is attached.
(3) Choose screws whose dimension allow fixing thread depth into track rail ℓ to be less than H_4.
(4) The direction of basic dynamic load rating (C), basic static load rating (C_0), and static moment rating (T_0, T_X, T_Y) are shown in the sketches below.
The upper values of T_X and T_Y are for one slide unit and the lower values are for two slide units in close contact.

Remarks 1. The identification numbers with * are our semi-standard items.
2. There is no oil hole on the slide unit.



1N≒0.102kgf

Example of identification number of assembled set

Model code		Dimensions	Part code		Model code	Preload symbol	Classification symbol	Interchangeable code	Supplemental code
MLF	C	6	C2	R120		T0	P		/D
①	②	③	④	⑤	①	⑥	⑦	⑧	⑨

① Model: MLF, LWLF, LWLF···N — Wide type
② Length of slide unit: C — Short; No symbol — Standard
③ Size: 2, 4, 6, 10
④ Number of slide unit (2)
⑤ Length of track rail (120 mm)
⑥ Preload amount: T0 — Clearance; No symbol — Standard
⑦ Accuracy class: H — High; P — Precision
⑧ Interchangeable: No symbol — Non-interchangeable specification; S1 — S1 specification; S2 — S2 specification
⑨ Special specification: A, BS, D, E, I, MN, N, Q, RE, S, W, Y

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Wide type

Shape: **MLF • LWLF**



Size	2	4	6	10	14
	18	24	30	42	





Tapped rail specification
LWLF···N



Identification number: MLF series	Identification number: LWLF series (No C-Lube)	Interchangeable	Mass (Ref.) g: Slide unit	Mass (Ref.) g: Track rail (per 100 mm)	Dimensions of assembly mm: H	H_1	N	Dimensions of slide unit mm: W_2	W_3	W_4	L_1	L_2	L_3	M_1×depth	H_3	Dimensions of track rail mm: W	H_4	M_2	d_3	d_4	h	E	F	Appended mounting bolt for track rail (2) mm: Bolt size× ℓ	Basic dynamic load rating (4): C N	Basic static load rating (4): C_0 N	Static moment rating (4): T_0 N·m	T_X N·m	T_Y N·m
MLFC 10		○	6.1	28	6.5	1.5	3.5	17	13	2	20.5	–	13.6	M2.5×1.5	1.3	10	4	–	2.9	4.8	1.6	10	20	Cross-recessed pan head screw for precision equipment (Class 3) M2.5×7	712	1 180	6.1	2.6 14.9	2.2 12.5
	LWLFC 10···B	○	5.9																										
MLFC 10···N*		–	6.1	29														M3 Through	–	–	–			M3× ℓ (3) (Not appended)					
	LWLFC 10···N*	–	5.9																										
MLF 10		○	7.6	28							24.5		17.6					–	2.9	4.8	1.6			Cross-recessed pan head screw for precision equipment (Class 3) M2.5×7	849	1 510	7.8	4.2 22.4	3.5 18.8
	LWLF 10···B	○	7.5																										
MLF 10···N*		–	7.6	29														M3 Through	–	–	–			M3× ℓ (3) (Not appended)					
	LWLF 10···N*	–	7.5																										
MLFC 14	LWLFC 14···B	○	13	54	9	2	5.5	25	19	3	22.5	–	13	M3 ×3	1.7	14	5.5	–	3.5	6	3.2	15	30	M3×8	1 240	1 700	12.2	3.8 24.6	3.2 20.7
MLFC 14···N*	LWLFC 14···N*	–		56														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
MLF 14		○	20	54							31.5	10	22					–	3.5	6	3.2			M3×8	1 770	2 840	20.3	10.1 54.7	8.4 45.9
	LWLF 14···B	○	21																										
MLF 14···N*		–	20	56														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
	LWLF 14···N*	–	21																										
MLFG 14		○	29	54							42	19	32.5					–	3.5	6	3.2			M3×8	2 320	4 160	29.8	21.0 104	17.6 87.6
	LWLFG 14···B	○	31																										
MLFG 14···N*		–	29	56														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
	LWLFG 14···N*	–	31																										

1N≒0.102kgf

Notes (1) Track rail lengths L are shown in Table 3.2 on page Ⅱ−11.
(2) The appended track rail mounting bolts are hexagon socket head bolts equivalent to JIS B 1176.
(3) Choose screws whose dimension allow fixing thread depth into track rail ℓ to be less than H_4.
(4) The direction of basic dynamic load rating (C), basic static load rating (C_0), and static moment rating (T_0, T_X, T_Y) are shown in the sketches below.
The upper values of T_X and T_Y are for one slide unit and the lower values are for two slide units in close contact.

Remarks 1. The specification of oil hole is shown in Table 13 on page Ⅱ−18.
2. The identification numbers with * are our semi-standard items.



Example of identification number of assembled set

Model code	Dimensions	Part code		Model code	Preload symbol	Classification symbol	Interchangeable code	Supplemental code
MLF	G	14	C2	R240		T1	P		/D
①	②	③	④	⑤	①	⑥	⑦	⑧	⑨

① Model

MLF	Wide type
LWLF···B	
LWLF···N	

② Length of slide unit

C	Short
No symbol	Standard
G	Long

③ Size: 10, 14

④ Number of slide unit (2)

⑤ Length of track rail (240 mm)

⑥ Preload amount

T0	Clearance
No symbol	Standard
T1	Light preload

⑦ Accuracy class

H	High
P	Precision

⑧ Interchangeable

No symbol	Non-interchangeable specification
S1	S1 specification
S2	S2 specification

⑨ Special specification: A, BS, D, E, I, LR, MN, N, Q, RE, S, W, Y

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Wide type

MLF • LWLF

Shape



Size					
2	4	6	10	14	
18	**24**	**30**	**42**		





Tapped rail specification
LWLF···N



Identification number		Interchangeable	Mass (Ref.) g		Dimensions of assembly mm			Dimensions of slide unit mm								Dimensions of track rail mm								Appended mounting bolt for track rail (2) mm	Basic dynamic load rating (4)	Basic static load rating (4)	Static moment rating (4)		
MLF series	LWLF series (No C-Lube)		Slide unit	Track rail (per 100 mm)	H	H_1	N	W_2	W_3	W_4	L_1	L_2	L_3	M_1×depth	H_3	W	H_4	M_2	d_3	d_4	h	E	F	Bolt size× ℓ	C N	C_0 N	T_0 N·m	T_x N·m	T_y N·m
MLFC 18	LWLFC 18···B	○	26	90	12	3	6	30	21	4.5	26.5	–	16.6	M3×3	2.5	18	7	–	3.5	6.5	4.5	15	30	M3×8	1 510	2 120	19.4	5.5 35.9	4.7 30.1
MLFC 18···N*	LWLFC 18···N*	–	26	92														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
MLF 18		○	42	90							38.5	12	28.6					–	3.5	6.5	4.5			M3×8	2 280	3 810	34.9	16.9 88.8	14.2 74.5
	LWLF 18···B	○	44																									
–	LWLF 18···BCS	○																										
MLF 18···N*		–	42	92														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
	LWLF 18···N*	–	44																									
MLFG 18		○	59	90					23	3.5	50.5	24	40.4					–	3.5	6.5	4.5			M3×8	2 870	5 300	48.5	31.9 159	26.7 134
	LWLFG 18···B	○	61																									
MLFG 18···N*		–	59	92														M4 Through	–	–	–			M4× ℓ (3) (Not appended)					
	LWLFG 18···N*	–	61																									
MLFC 24		○	46	139	14	3	8	40	28	6	30.5	–	17.7	M3×3.5	3.2	24	8	–	4.5	8	4.5	20	40	M4×10	2 800	3 340	40.7	9.7 67.6	8.2 56.8
	LWLFC 24···B	○	45																									
MLF 24		○	74								44	15	31												4 310	6 200	75.6	30.6 168	25.7 141
	LWLF 24···B	○	76																									
–	LWLF 24···BCS	○																										
MLFG 24		○	108								59	28	46.3												5 620	9 060	111	63.3 321	53.1 270
	LWLFG 24···B	○	111																									

Notes (1) Track rail lengths L are shown in Table 3.2 on page Ⅱ−11 and Table 3.3 on page Ⅱ−12.
(2) The appended track rail mounting bolts are hexagon socket head bolts equivalent to JIS B 1176. For stainless steel model, stainless steel bolts are appended.
(3) Choose screws whose dimension allow fixing thread depth into track rail ℓ to be less than H_4.
(4) The direction of basic dynamic load rating (C), basic static load rating (C_0), and static moment rating (T_0, T_x, T_y) are shown in the sketches below.
The upper values of T_x and T_y are for one slide unit and the lower values are for two slide units in close contact.

Remarks 1. The specification of oil hole is shown in Table 13 on page Ⅱ−18.
2. The identification numbers with * are our semi-standard items.



Example of identification number of assembled set

Model code	Dimensions	Part code		Model code	Material code	Preload symbol	Classification symbol	Interchangeable code	Supplemental code
MLF	G	18	C2	R300			T1	P		/D
①	②	③	④	⑤	①	⑥	⑦	⑧	⑨	⑩

① Model

MLF	Wide type
LWLF···B	
LWLF···N	

② Length of slide unit

C	Short
No symbol	Standard
G	Long

③ Size: 18, 24

④ Number of slide unit (2)

⑤ Length of track rail (300 mm)

⑥ Material type

No symbol	Stainless steel made
CS	High carbon steel made

⑦ Preload amount

T0	Clearance
No symbol	Standard
T1	Light preload

⑧ Accuracy class

H	High
P	Precision

⑨ Interchangeable

No symbol	Non-interchangeable specification
S1	S1 specification
S2	S2 specification

⑩ Special specification: A, BS, D, E, I, LR, MN, N, Q, RE, S, U, W, Y

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch

Wide type

MLF • LWLF

Shape



Size					
	2	4	6	10	14
	18	24	30	42	





Identification number		Interchangeable	Mass (Ref.) g		Dimensions of assembly mm			Dimensions of slide unit mm									Dimensions of track rail mm									Appended mounting bolt for track rail (2) mm	Basic dynamic load rating (3)	Basic static load rating (3)	Static moment rating (3)		
MLF series	LWLF series (No C-Lube)		Slide unit	Track rail (per 100 mm)	H	H_1	N	W_2	W_3	W_4	L_1	L_2	L_3	L_4	M_1×depth	H_3	W	H_4	W_5	W_6	d_3	d_4	h	E	F	Bolt size× ℓ	C	C_0	T_0	T_x	T_y
																											N	N	N·m	N·m	N·m
MLFC 30	LWLFC 30···B	○	70	198	15	3	10	50	35	7.5	35.5	–	20.5	40	M4×4.5	3.1	30	9	–	–	4.5	8	4.5	20	40	M4×12	3 890	4 540	69.1	15.4 107	13.0 89.9
MLF 30		○	111								49.5	18	34.8	54													5 970	8 440	128	48.7 256	40.8 215
	LWLF 30···B	○	112																												
–	LWLF 30···BCS	○																													
MLFG 30		○	167								68.5	35	53.8	73													7 810	12 300	187	100 508	84.3 426
	LWLFG 30···B	○	170																												
MLFC 42		○	95	294	16	4	9	60	45	7.5	41.5	–	25.7	46	M4×4.5	3.2	42	10	23	9.5	4.5	8	4.5	20	40	M4×12	5 440	6 810	144	30.8 180	25.8 151
	LWLFC 42···B	○											25.3														5 030	6 050	128	24.8 164	20.8 137
MLF 42		○	138								55	20	39.4	60													7 050	9 840	209	61.3 333	51.4 280
	LWLF 42···B	○	140										39																		
–	LWLF 42···BCS	○																													
MLFG 42		○	200								74.5	35	58.7	79													9 520	15 100	321	140 674	117 565
	LWLFG 42···B	○	204										58.3														9 200	14 400	305	126 644	106 541

Notes (1) Track rail lengths L are shown in Table 3.2 on page Ⅱ−11 and Table 3.3 on page Ⅱ−12.

(2) The appended track rail mounting bolts are hexagon socket head bolts equivalent to JIS B 1176. For stainless steel model, stainless steel bolts are appended.

(3) The direction of basic dynamic load rating (C), basic static load rating (C_0), and static moment rating (T_0, T_x, T_y) are shown in the sketches below.
The upper values of T_x and T_y are for one slide unit and the lower values are for two slide units in close contact.

Remark: The specifications of grease nipple are shown in Table 14 on page Ⅱ−18.



Example of identification number of assembled set

Model code	Dimensions	Part code		Model code	Material code	Preload symbol	Classification symbol	Interchangeable code	Supplemental code
MLF	G	42	C2	R320			T_1	P		/D
①	②	③	④	⑤	①	⑥	⑦	⑧	⑨	⑩

① Model

MLF	Wide type
LWLF···B	

② Length of slide unit

C	Short
No symbol	Standard
G	Long

③ Size: 30, 42

④ Number of slide unit (2)

⑤ Length of track rail (320 mm)

⑥ Material type

No symbol	Stainless steel made
CS	High carbon steel made

⑦ Preload amount

T_0	Clearance
No symbol	Standard
T_1	Light preload

⑧ Accuracy class

H	High
P	Precision

⑨ Interchangeable

No symbol	Non-interchangeable specification
S1	S1 specification
S2	S2 specification

⑩ Special specification: A, BS, D, E, Ⅰ, LR, MN N, Q, RE, S, U, W, Y

1N=0.102kgf=0.2248lbs.
1mm=0.03937inch